No. CE-RO/LKO/US/NH-29E (New NH-24)/Km.89.000-Km.94.800/2024 Government of India Ministry of Road Transport &Highways (Chief Engineer - Regional Office, Lucknow) N.H. Bhawan, Biotech Chowk, Lucknow Ring Road,Vikas Nagar, Lucknow - 226 022 Ph.: (0522) - 2967112, 2738226 (Tele-Fax)

Dated: 02.09.2024

Invitation of public comments

Sub.: Providing NOC for laying 100 mm MDPE gas pipeline on NH-29E (New NH-24) from km. 89.000 to km. 94.800 at District - Gorakhpur in the state of Uttar Pradesh - Reg

M/s Torrent Gas Ltd. has submitted the proposal for laying 100 mm MDPE gas pipeline on NH-29E (New NH-24) from km. 89.000 to km. 94.800 at District - Gorakhpur in the state of Uttar Pradesh to Executive Engineer, NH Division, PWD, Gorakhpur for consideration.

2. The above proposal has been examined in this office in light of Ministry guidelines issued vide OM no.RW/NH-33044/29/2015/ S&R(R) dated 22.11.2016 & NH-36094/01/2022-S&R (P&B) dated 24.04.2023. The application shall be put out in the public domain for 30 days for seeking claims and objections (on grounds of public inconvenience, safety and general public interest).

3. In view of the above, comments of the public on the above application (checklist enclosed) is invited to the below mentioned address:

The Chief Engineer - Regional Officer, Ministry of Road Transport & Highways, N.H. Bhawan, Biotech Chowk, Lucknow Ring Road, Vikas Nagar, Lucknow - 226 022.

Encl.: As above.

Yours faithfully,

(Ritesh Yadav) Assistant Executive Engineer for Chief Engineer - Regional Officer

Copy to:

- (i) NIC, New Delhi for uploading on the Ministry's website.
- (ii) The Chief Engineer (NH), Public Works Department, NirmanBhavan, 96, M. G. Marg, Lucknow - 226 001.

(Ritesh Yadav) Assistant Executive Engineer for Chief Engineer - Regional Officer

CHECK-LIST

Guidelines for Project Directors for processing the proposal for Laying of Natural Gas 100 mm MDPE pipeline in the land along National Highway No.-29 E (New NH-24) Gorakhpur-Nautanwa Road.

Relevant Circulars

- 1. Ministry Circular No. RW/NH/33044/29/2015/S&R dated 22.11.2016.
- 2. Ministry Circular No. RW/NH/33044/27/2005/S&R (R) (RT)dated 06.08.2013.

Check list for getting approval for laying of Natural Gas 100 mm MDPE pipeline in the land Along National Highway 29 E (New NH-24)

Sr.No.	Item	Information/ Status	Remarks
1	General Information		
1.1	Name and Address of the Applicant / Agency	M/s Torrent Gas Limited office at Prashant Tower, opposite old Transport Nagar Police Chowki, Mehwa Chungi, Gorakhpur- Lucknow Road, Gorakhpur-273016	
1.2	National Highway Number	NH- 29E (NH-24)	
41.3	State	Uttar Pradesh	
51.4	Location	Gorakhpur	
1.5	(Chainage in km)	CH 89+000 to 94+800	
1.6	Length in Meters	Along NH-24 Left Side – 5.800 Km Across NH-24 Length-0.060 Km	
1.7	Width of available ROW in both side		
	(a) Right side from center line towards increasing chainage/km direction	11 mtrs	
1.8	Proposal to lay underground Natural MDPE pipeline	MORTH	
	(a) Right side from center line towards increasing chainage/km direction	11 mtrs	
1.9	Proposal of acquire land		
	(a) Right side of center line	N.A.	, dv
	(b) Left side of center line	N.A.	N
	TO RAFE	सहायके अभियन्ता अधिशास	नी अभियन्ता ण्ड, लो०नि०वि०

गौरखपुर

गोरखपूर

MIT

1.10	Whether proposal in the same side where land is not to be acquired	NO acquisition of land required	
	If not, then where to lay the pipeline	Along & Across the National Highway	
1.11	Details of already laid services, if		
	any, along the proposed route		
1.12	No of lanes (2/4/6/8) existing	4	
1.13	Proposed Number of lane (2 lanes	NIL	
	with paved shoulder 4/6/8 lanes)		
1.14	Service road existing or not		
	If yes, then which side		
	(a) Left side from center line	Does not exist	
	(b) Right side from center line	Does not exist	
1.15	Proposed service road		
	(a)Left side from center line	Not proposed	
	(b) Right side from center line	Not proposed	
1.16	Whether proposal to lay gas pipeline is after the service road or between	Between road edge and utility duct	
	the service road main carriageway	1	
1.17	The Permission for laying of Gas pipeline shall be considered for approval / rejection based on the Ministry Circular mentioned as above.		
	 (a) Carrying of Gas pipeline on Highway bridges shall not be permitted as gases pipes can accelerate the process of corrosion or may cause explosions, thus, being much more injurious than leakage of gas. 	N.A.	2 2 2 2
	(b) Carrying of gas pipelines on bridges shall also discouraged however if the gas supply authorities seem to have no other viable alternative and approach the highway authority well in time before the design of the bridge in finalized they may be permitted to carry the pipeline on independent super structure supported on extended portion of piers and abutments in such a manner	N.A.	anot
			शासी अभियन्ता २ खण्ड, लो०नि०विल गोरखपुर

 \bigcirc

	that in the final arrangement enough free spade around the super structure of the bridge remains available for inspection			
	 and repairs etc. (c) Cost of required extension of the substructure as well as that of the supporting super structure shall be borne by the agency-in-charge of the utilities. 	N.A.		
	 (d) Services are not being allowed indiscriminately on the parapet /any part of the bridges; safety of the bridge has to be kept in view while permitting various services along bridge. Approvals 	N.A.		
1.10	to be accorded in this regard with the concurrence of the Ministry 's Projects Chief Engineers Only	200	- ¢	
1.18	If Crossing of the road involved If yes, it shall be either encased in	YES YES		
	pipes or through structure or conduits specially built for that purpose at the expensed of the agency owing the line		. 2	
	 a) Existing drainage structures shall not be allowed to carry the lines 	YES		
	b) Is it on a line normal to NH	YES		
	 c) Crossings shall not be too near the existing structures on the national highway, the minimum distance being 15 meters. What is the distance from the existing structures 	YES		
	 d) The casing pipe (or Conduit pipe in the case of electric /OFC cable) carrying the utility line shall be of steel, case iron, or reinforced cement concrete and have 	YES		
,	adequate strength and be large enough to permit ready withdrawal of the carrier pipe/cable	Anth	A.	ma
8	THE REAL	सहायक अभियन्ता राठमा० ख्रण्ड, लो०नि०वि० गोरखपुर	आधिश रा॰मा॰	ासी अभियन्ता खण्ड, लो०नि०वि० गोरखपुर

	e) Ends of the casing/conduit	YES
	pipe shall be sealed form the	
	outside, so that it does not	and the second
	act as drainage path.	
	f) The casing /conduit pipe	YES
	should, as minimum extend	Sec
	from drain to drain in cuts	
	and toe of slope toe of slope	
	in the fills	
	g) The top of the casing	YES
	/conduit pipe should be at	
	least 1.2 meter below the	the second se
	surface of the road subject	
	to being at least 0.3 m below	
	the drain inverts.	
	h) Crossing shall be by boring	YES
	method (HDD) especially	
	where the existing road	
9	pavement 'is of cement	
	concrete or dense	
	bituminous concrete type	
	i) The casing /conduit pipe	YES
	shall be installed with an	
9	even bearing throughout its	
	length and in such a manner	
	as to prevent the formation	
	of a waterway along it.	
2	Document /Drawings enclosed	YES
	with the proposal.	
2.1	Cross section showing the size of	N.A.
	trench for open trenching method (Is	
	its normal size of 1.2 m deep x 0.3	
	wide)	
	I. Should be greater than	N.A.
	60Cm wider than outer	
		12 I
	diameter of the pipe	
	II. Located as close to the	N.A.
	extreme edge of the right-of	
	way as possible but not less	
	than 15 meters from the	
	centerlines of the nearest	
	carriageway.	
	III. Shall not be permitted to run	N.A.
	along the national Highways	
	when the road formation is	
	situated in double cutting.	N.A.
	At 18 M.	mo pr
		सहायक अभियन्ता अधिशासी अभियन्तो
	1015 BALA	रा०मा० ख्रण्ड, लो०नि०वि० रा०मा० खण्ड, लो०नि०विव

LWIT

 \bigcirc

ख्रण्ड, लो०नि**०वि०** गोरखपुर de

खण्ड, लार गोरखपुर

RI

	Nor shall these be laid over the existing culverts and bridges.	-
	IV. These should be so laid that their top is least 0.6 meter below the ground level so as not to obstruct drainage of the road land.	N.A.
2.2	Cross section showing the size of pit and location of pipe for HDD method	Attached
2.3	Strips plan/Route Plan showing Gas Pipeline, Chain age, width of ROW, distance of proposed, cable from the edge of ROW, important milestone, Intersections, cross drainage work etc.	Incorporated in the drawing
2.4	Methodology for laying of showing Gas pipeline	HDD
2.4.1	Open Trenching method. (May be allowed in utility corridor only where pavement is neither cement concrete nor dense bituminous	N.A.
1	concrete type. If yes, Methodology of refilling of trench.	
	a. The trench width should be at least 30 cm, but not more than 60 cm wider than the outer diameter of the pipe.	N.A.
	b. For filling of the trench, Bedding shall be to a depth of not less than 30 cm. it shall consists of granular material free of lumps, clods and cobbles and graded to yield a firm surface without sudden change in the bearing value unsuitable soil and rock edged should be excavated and replaced by selected material.	N.A.
	c. The backfill shall be completed in two stages (i) side fill to the level of the top to the pipes and (ii) overfill to the bottom of the road cructo	ASS Jones
	HEAT STORE	सहायक अभियन्ता अधिशासी अभियन्ता रा०मा० खण्ड, लो०नि०वि० गोरखपुर गोरखपुर

Ó

	d. The side fill shall consist of granular material laid in 15 cm layers each consolidated by mechanical tampering and controlled addition of moisture to 95% of the Proctor's Density. Over fill shall be compacted to the same density as the material that had been removed. Consolidation by saturation or pending will not be permitted		
	e. The road crust shall be built to the same strength as the existing crust on either side of the trench; care shall be taken to avoid the formation of a dip at the trench.		
	f. The Excavation shall be protected by flagman, sings and barricades, and red lights during night hours	N.A.	21
	g. \If required, a diversion shall be constructed at the expensed of agency owing the utility line	N.A.	
2.4.2	Horizontal Directional drilling (HDD) Method	YES	
2.4.3	Laying of Gas Supply Pipeline through CD works and method of laying	YES	
	a. On approaches, the water mains/cable shall be carried along a line as close to the edge of the right-of way as possible up-to a distance of 30 m from the bridge and subject to all other stipulation contained in this Ministry's guidelines issued with letter No. NH-HI/P66/76 dated 19.11.1976	YES	
3	Draft License Agreement signed by two witnesses	YES	, Ø
4	Performance bank Guarantee in favor of NHAI has to be obtained	To Bosh	howe
	A CONTRACTOR	ः सहायक अभियन्ता तिमाव खण्ड, तोवनिवविव गोरखपुर	अधिशासी अभियन्ता राज्याo खण्ड, लो०नि०वि० गोरखपुर

 \bigcirc

	Protonal highway hight Of Ways.	1 AAN CONTRACT	पक अभियन्ता खण्ड, लो०नि०वि०	अधिशासी उ	। भभियन्त
	work if installation, shifting or repairs, or alteration to the showing Gas Supply pipeline located in the National Highway right –or-ways.				N
5.9	Prior approval of the NHAI shall be obtained before undertaking any	YES		4	
5.8	If any claim is raised by the Concessionaire, then the same has to be paid by the applicant	YES	*		
5.7	Traffic movement during laying of Gas supply pipeline to be managed by the applicant	YES			
5.6	Indemnity against all damages and claims clause (xxiv)	YES			
5.5	Shifting due to 8 lining/widening of NH	YES			
5.4	Shifting of Gas Supply pipeline as and when required by NHAI at their own cost	YES			
5.3	Confirming all standard condition of NHAI'S guideline	YES			-
5.2	to NHAI or to the concerned agency Renewal of Bank Guarantee				
5.1	Not to Damage to other utility, if damaged then pay the losses either	YES	· · ·		
5	Affidavit/undertaking from the application	- S			
4.2	Confirmation of BG has been obtained as per NHAI Guidelines				
4.1	Performance BG as per above is to be obtained		÷		
	away from the edge of the right of way. No payment shall be payable by the NHAI to the licensee for clearing debris /loose earth.				
	/loose earth produced due to execution of trenching at least 50 m				
	good the excavated trench for laying the cables /ducts by proper filling and compaction, clearing Debris				
	till satisfactory completion of work) as security for ensuring /making				
	crossing of NH, for a period of one year initially (extendable if required				
	@Rs100/- per running meter (parallel to NH) and Rs100000/-per				

 \bigcirc

5.10	Expenditure, if any, incurred by NHAI for repairing any damage caused to the National Highway by the laying,	YES
	maintenance or shifting of the Gas supply pipeline will be borne by the agency owing the line.	
5.11	If the NHAI considers it necessary in future to move the utility line for any work of improvement or repairs to the road, it will be carried out as	YES
	desired by the NHAI at the cost of the agency owing the utility line within a reasonable time (not exceeding 60 days) of the intimation given.	
5.12	Certificate from the application in the following format	
	 Laying of Gas supply pipeline will not have any deleterious effects on any of the bridge components and roadway safety for traffic. 	YES
	For 6-laning "We do undertake that I will relocate service road/approach road /utilities at my own cost	YES
	notwithstanding the permission granted with such time as will be stipulated by NHAI "for future six- lining or any other development."	
6	Who will sign the agreement on behalf of gas supply pipeline agency?	Authorized Signatory Torrent Gas Limited
7	Certificate from the Project Director	
7.1	Certificate for confirming of all standard condition issued vide Ministry circular no NH-41.(58)/68 dated 31.01.1969, Ministry circular no. RW/NH-III/P/66/76 dated 18/ 19.11.1976, Ministry Circular	Attached
	NO.RW/NH-1103/1/86-DOI (ii) Dated 28.07.1993. Ministry circular No. RW/NH- 34066/2/9 S&R dated 25.10.1999 and Ministry Circular No. RW/NH-330231/19/99 dated	E Que Don

λĸ

भ गोरखपुर

31

The above particulars along with the drawing and documents has been verified and certified as correct as per prevailing site conditions.

anot

Name designations & Signature of the Authorized representative of applicant

अधिशासी अभियन्ता Name designation खुण्ड, ⁸लोo सिंहा adure concerned field authoritin सर्द भूम-PWD of the

X

सहायक अभियन्ता रा०मा० खण्ड, लो०नि०वि० गोरखपुर