

भारतीय राष्ट्रीय राजमार्ग प्राधिकरण

(सड़क परिवहन एवं राजमार्ग मंत्रालय, भारत सरकार)

National Highways Authority of India

(Ministry of Road Transport & Highways, Govt. of India)

क्षेत्रीय कार्यालय-पश्चिम उ०प्र०, लखनऊ

Regional Office - West UP, Lucknow.

3/248, विशाल खण्ड, गोमती नगर, लखनऊ—226010 (उ.प्र.)

3/248, Vishal Khand, Gomti Nagar, Lucknow-226010 (UP)

19001/1/RO-W-UP/NH-509/765KV/KM.118-119/UG/209

दूरभाष / Phone : 0522-4960291

टेलीफैक्स / Fax : 0522-4950680

ई—मेल / E-mail : rowestup@nhai.org

rowestup@gmail.com

वेबसाइट / Website : www.nhai.gov.in

Dated: 19.05.2020

Invitation of Public Comments

Sub: Proposal for permission for Overhead Power Line crossing of NH-509 (Old NH-93) between km. 118.00 and Km. 119.000 near village-Danpur, Tehsil-Dibai, District- Bulandshahr by U/C 765 KV S/C Ghatampur TPS - Transmission line.

The Authorized Signatory M/s Ghatampur Transmission Limited, Gautambuddh Nagar has submitted the proposal for permission for Overhead Power Line crossing of NH-509 (Old NH-93) between km. 118.00 and Km. 119.000 near village-Danpur, Tehsil-Dibai, District- Bulandshahr by U/C 765 KV S/C Ghatampur TPS - Transmission line in the State of Uttar Pradesh.

- 2. From the submitted proposal, it is seen that the crossing is proposed at Ch. 118.637 (between km. 118.00 and Km. 119.000) near village-Danpur, Tehsil-Dibai, District-Bulandshahr on NH-509 (Old NH-93) for total length of 220.9 meter. The height of both proposed structures (Transmission Towers) on which the proposed overhead line is hanging is 53.43m & 53.47m respectively. The structures (Transmission Towers) on either side are being erected at distance of 115.33m & 105.57m from centre of the NH. Width of available ROW is 40m. Left side from Center Line towards increasing chainage/KM direction 20m and Right side from Center Line towards increasing chainage/KM direction 20m. Vertical clearance of the overhead lines of ground level is 22.90m. However, the proposed transmission line shall be crossing the National Highway at 76°0'00" angle.
- 3. As per the guidelines, issued by the Ministry vide OM No.RW/NH-33044/29/ 2015/ S&R(R) dated 22.11.2016, the application shall be put out in the public domain for 30 days for seeking claims and objections (on grounds of public inconvenience, safety and general public interest).
- 4. In view of the above, comments of the public on the above application is invited to the below mentioned address, which should reach by this office within 30 days from the date of publication beyond which no comments shall be entertained.

The General Manager cum Regional Officer, National Highways Authority of India Regional Office, UP-West, Lucknow 3/248, Vishal Khand, Gomti Nagar Lucknow-226 010

This issue with the approval of RO-West (UP).

Encl: As above.

(Pankaj Kumar) DGM (T) For RO-West, UP

Copy to:

1. Web Admin, NHAI-HQ- with request for uploading on the NHAI website.

2. The Technical Director, NIC, Transport Bhawan, New Delhi- with request for uploading on the Ministry's website.

3. The Authorized Signatory M/s Ghatampur Transmission Limited, Gautambuddh Nagar (UP) for information.

4. The PD, PIU-Moradabad for information.

"Building a nation, not just Roads."

CHECK LIST

Project Director for processing the Proposal of lane over head electrical line crossing national highways vested with NHAI.

Circular / Codes:-

Ministry Circular No NH-III/p/20/77 dated 08-04-1982 Indian Electricity Act 1910 Indian Electricity Rules 1956

IRC: 32-1969

IS:5613-1976 Part I to IV

For getting approval for layering of overhead electrical line along the National Highways NH-93(509), vested with NHAI.

S.NO	<u>ltem</u>	Information/ status	Remark
	General Information	765 KV S/C (QUAD) GHTL	
1	Name and address of the applicant	Ghatampur Transmission LTD; H.N-B-218, Sigma-1, Gautambuddh Nagar, U.P – 201308	- ('
2	National Highway No	NH 93(509)	
3	State	Uttar Pradesh	
L.4	Location	Danpur Village, Bulandshar district.	
<u>5</u>	Type of electric including carrying voltage details and purpose	765 KV S/C (QUAD) GHTL	
L.6	Chain -age in Kilometers	37.5 118 . 637	
1.7	Length in Metre	220.9	
1.8	Width of available ROW	40 Mtr.	
	(a). Left side from Center Line towards increasing chainage / KM Direction	20 Mtr.	
	(b) Right side from Center Line towards increasing chainage / KM Direction	20 Mtr.	<u> </u>
1.9	Proposal to lay Overhead		
	 (a) Left side from Center Line towards increasing chainage / KM Direction (b) Right side from Center Line towards increasing chainage / KM Direction (c) Erection of Electrical line along the NH 91 	AP195A/O at a distance of 115.33 Mtr. from centre of Road. AP195B/O at a distance of 105.57Mtr. from centre of Road. NA	
1.10	Proposal to acquire land	NA	
	(a)Left side from Center Line		
	(b)Right side from Center Line		
1.11	Whether the proposal is a- in the same side where land is not to be acquired b- Crossing the National Highway If not then where to lay the overhead electrical line	Yes. Crossing the National Highway. Towers shall be constructed outside NHAI Land Boundary.	
1.12	Details of Already laid services (overhead telecommunication line, overhead		
	electric line etc), if any, along the proposed route / proposed crossing	N/A	
1.13	NO of lanes (2/4/6/8 lanes) existing	02 lane.	
1.14	Proposed number of lanes (2 lanes with paved shoulder 4/6/8 lanes)	N/A	

परियोजना गिर्देशका Pro का Different प्रार्थित राष्ट्रीय राजमान प्राधिकरण भारतीय राष्ट्रीय राजमान प्राधिकरण National Highway Authority of India मुराबाबार /Moradabad

L.15	Service Road existing or not	No Service Road.	
	If yes then which side		
	a) Left side from center line	N/A	
	b) Right side from center line	N/A	
1.16	Proposed Service Road	N/A	
	a) Left side from center line		
	b) Right side from center line		
1.17	Whether proposal to lay overhead electric line is after the service road or between the service road and main carriage way, or crossing for approval / rejection based on the Ministry circulars and relevant codes mentioned as above.	Overhead Electric Transmission Line crossing the NH-93(509).	
1.19	I- If crossings of the roads involved	Yes	
	(a) Crossing angle for NH and provide length along the Highway(b) Structure (Tower, pole and for HT Line only tension towers) for	(a) 76°0′00″,220.90 Meters	
	crossings shall not be too near the existing structures on the National	(b) Distance more than	
	Highway, The minimum distance being 15 meter.	115.33Mtr & 105.57	
	(i)- Type of Existing / proposed structure for National Highways	Mtr. from centre of	
	(ii)- What is the distance of tower, pole and tension tower lying from the	Road.	
	existing / proposed structure for National Highways.	(i) HT Tower 53.43	
		(ii) 115.33 Mtr &	
		105.57 Mtr. from	
		centre of the NH.	
-	(c)- The overhead lines and their supporting poles / towers should ordinarily be	N/A. Towers shall be	
	placed at the extreme age of the road land boundary. In any case, these shall	constructed at a distance of	
	be atleast 10 meter away for the age of the existing shoulders of extreme	115.33 Mtr. (RS) & 105.57Mtr.	
	be alleast to fileter away for the age of the existing shoulders of empirimum	(LS) towards increasing	
	traffic lane. Where the existing road way is narrower than the minimum	chainage direction from	
	according to standard or where the widening is proposed for any reason the	centre of Road towards	
	lateral clearance shall be reckoned with respect to ultimate road way.	increasing Chainage direction.	
	What is the horizontal clearance from the extreme edge of the road land boundary?		
	(d)The overhead lines and their supporting poles/ towers should originally be	N/A. Towers shall be	
	placed at the minimum distance of 5.0 m from the nearest line of avenue	constructed at a distance of	
	trees.	113.33 Mill. (U2) & 103.37	
	tiees.	Mtr. (LS) towards increasing	
	the nearest line of avenue trees?	chainage direction from	
	What is the horizontal clearance from the nearest line of avenue trees?	centre of Road towards	
		increasing Chain age	
		direction.	
	(e)- in mountainous / hilly terrain the over head lines should be erected	Plain terrain.	
	preferably on the valley side as far away as practicable .In hilly reason, label of		
	ground at a suitable distance below the outer conductor on either side from	1	
	the central line is also to be noted and marked in profile so as to ensure		
	required ground clearance underneath conductor and side clearances in swung	7	
	conditions. Is the proposal in hilly area?		
	The horizontal clearances in respect of poles erected for the purpose of stree		
	lighting in Urban situations shall be as under:-	1111	
	i-For roads with Minimum 300mm from the	N/A	
	Raised kerbs 300mm from the aged of nearest		
385	kerb Preferably 600mm	ARANSMIS.	
	वरियोजना स्थितिन भारतीय सन्दर्भय रा National Highway मुरादाबाद /M	AUTHORITA AND COM	

	ii- For roads with At least 1.5m from the edge of the carriage way ,	N/A	
	raised kerbs subject to minimum of 5.0 from the central line		
	of the carriage way .		
	(g) the Pylons of III lines along crossing the road shall be a	N/A	
	NH land (h) for crossing the line of same voltage or lower voltage , suspension/ tension tower with suitable extensions shall be used .	YES. Tension Towers with suitable extension shall be used.	
	(i) The vertical clearance of the overhead lines crossing the road shall be reckoned from the top of the crown of the road taking into account the anticipated final top level due to future raising of road level, strengthening of pavement etc. The actual ground clearance of High Tension line for voltage above 650 voltes varies depending upon the voltage transmitted and these are stipulated in Indian standard. Codes is 56130-1976 part 1 to IV and Indian Electricity Rules 1956 as under.	22.90 Mtr. Ground Clearance shall be taken jointly with GTL and NHAI after completion.	
	Affidavit / Under taking to be obtained from (to be furnished by the applicant).	Yes	
2.1	Not to damage to other utility, if damaged then to pay the losses either to NHAI or to the concerned agency	Yes	
,	Under Taking for Renewal of Bank Guarantee if required.	Yes	
2.2	Confirming all standard conditions as laid down in ministry circular no- NH-	Yes	
2.3	III/P/20/77 dated 08-04-1982 Indian Electricity Act 1910 Indian Electricity Rules 1956 IRC :32-1969, IS : 5613-1976 part I to IV of (NHAI)		
2.4	Shifting of overhead Electrical line at their own cost as an when required by (NHAI)	Done by GTL electrical Department by own cost	
2.5	Shifting of overhead Electrical line at their own cost as an when required due to 4/6 lanning/ widening of NH	Done by GTL electrical Department by own cost	
2.6	Indemnity against all damage and claims whatsoever kind that may be to NHAI or to any third party in the row during installation, operation and maintenance	Done by GTL electrical Department by own cost	
2.7	Traffic movement during laying of OFC/Cable to be managed by the applicant	Done by GTL electrical Department by own cost	
2.8	If any claim is raised by the concessionaire then the same has to be paid by the applicant.	Done by GTL electrical Department by own cost	
2.9	Prior approval of the NHAI shall be obtained before undertaking any work of	Yes	
	installation, shifting or repairs, or alterations to the overhead electrical line located in the National Highway right of way.		
2.10	Expenditure, if any , incurred by electric department for repairing any damage caused to the National Highway by the laying , maintenance or shifting of the overhead electrical line located in the National Highway right of the way	1	

परियोजना निवेशक Project Director भारतीय राष्ट्रीय राजमार्ग प्राधिकरण National Highway Authority of India मुरादाबाद /Moradabad

If the NHAI considers it necessary in future to move the utility line for any	Yes	
work of improvement or repairs to the road , it will be carried out as desired		
by the NHAI at the cost of the electric department owing the utility line	9	
within a reasonable time (not exceeding 60 days) of the intimation given	ē.	
Certificate from the applicant in the following format :-	Yes	
(i) Laying of overhead electrical will not have any deleterious		
effects on any of the bridge components and roadway	8 " "	
safety for traffic.	.a es	
(ii) For 4/6 laning "we do undertake that I will relocate service	· ·	
	¥ ×	0.5
	al .	
	Vec	
	ii · · · · · · · · · · · · · · · · · ·	
The applicant ensures the safety of the Highway traffic against the	Yes	
Hazards of the high voltage lines during installation , operation and		
maintenance		
Undertaking the compliance with Indian electricity rules and other	Yes	
authorities, regulations- all over head lines shall comply with the		
requirement of the Indian electricity act and rules made their under		
and the regulations or specification as laid down by NHAI.	V	
		1
100/ per rupping meter (Parallel to NH) and Rs 1 00 000/- per crossing		
of NH for a period of one year initially(extendable if required till		-
satisfactory completions of work) as a security for insuring/ making		
good the area, Clearing debris / loose earth etc produced in the right of	*	
way. No payment shall be payable by the NHAI to the license for		3
clearing debris/ loose earth.		
Strip plan/ route plan showing overhead electrical line, chainage with of	Yes	
ROW, distance of proposed, structure(tower, pole and for HT Line only tension		
	a form	
Certificate for confirming that the proposal has been examined with	Yes	
respect to the structures and developmental work considered at this	6 1 2 18	
location and compliance of the standard conditions issued vide ministry	8 2	
circular no- NH-III/P/20/77 dated 08-04-1982 Indian Electricity Act 1910	2 = 3	2 0
Indian Electricity Rules 1956 IRC :32-1969, IS : 5613-1976 part I to IV of	A 16	
(NHAI) and NHAI's guideline.		
Certificate from PD In the following format:-	N/A	
Certificate from PD In the following format:- (i)- "it is certified that any other location of the electric line would be		
Certificate from PD In the following format:- (i)- "it is certified that any other location of the electric line would be extremely difficult and unreasonable costly and the installation of		
Certificate from PD In the following format:- (i)- "it is certified that any other location of the electric line would be		
	by the NHAI at the cost of the electric department owing the utility line within a reasonable time (not exceeding 60 days) of the intimation given Certificate from the applicant in the following format: (i) Laying of overhead electrical will not have any deleterious effects on any of the bridge components and roadway safety for traffic. (ii) For 4/6 laning "we do undertake that I will relocate service road/ approach road, utilities at my own cost, notwithstanding the permission granted within such time as will be stipulated by NHAI" for future 6 laning or any other development. The transmission line installation shall be carried out by trained and experienced personnel and supervised by technically qualified persons competent to undertake such work. The applicant ensures the safety of the Highway traffic against the Hazards of the high voltage lines during installation, operation and maintenance Undertaking the compliance with Indian electricity rules and other authorities, regulations- all over head lines shall comply with the requirement of the Indian electricity act and rules made their under and the regulations or specification as laid down by NHAI. Other documents and drawing to be furnished by the applicant Methodology for laying of overhead electric line. Draft license agreement Performance bank guarantee in favor of NHAI has to be obtain at the Rs 100/- per running meter (Parallel to NH) and Rs 1,00,000/- per crossing of NH, for a period of one year initially(extendable if required till satisfactory completions of work) as a security for insuring/ making good the area, Clearing debris / loose earth etc produced in the right of way. No payment shall be payable by the NHAI to the license for clearing debris/ loose earth. Strip plan/ route plan showing overhead electrical line, chainage with of ROW, distance of proposed, structure(tower, pole and for HI Line only tension towers) from the edge of ROW, important milestone, intersections, cross drainage works any other structure existing of propose	by the NHAI at the cost of the electric department owing the utility line within a reasonable time (not exceeding 60 days) of the intimation given Certificate from the applicant in the following format: (i) Laying of overhead electrical will not have any deleterious effects on any of the bridge components and roadway safety for traffic. (ii) For 4/6 laning "we do undertake that I will relocate service road/ approach road, utilities at my own cost, notwithstanding the permission granted within such time as will be stipulated by NHAI" for future 6 laning or any other development. The transmission line installation shall be carried out by trained and experienced personnel and supervised by technically qualified persons competent to undertake such work. The applicant ensures the safety of the Highway traffic against the Hazards of the high voltage lines during installation , operation and maintenance Undertaking the compliance with Indian electricity rules and other authorities, regulations- all over head lines shall comply with the requirement of the Indian electricity act and rules made their under and the regulations or specification as laid down by NHAI. Other documents and drawing to be furnished by the applicant Methodology for laying of overhead electric line. Performance bank guarantee in favor of NHAI has to be obtain at the Rs 100/- per running meter (Parallel to NH) and Rs 1,00,000/- per crossing of NH, for a period of one year initially(extendable if required till satisfactory completions of work) as a security for insuring/ making good the area, Clearing debris / loose earth etc produced in the right of way. No payment shall be payable by the NHAI to the license for clearing debris/ loose earth. Strip plan/ route plan showing overhead electrical line, chainage with of ROW, distance of proposed, structure(tower, pole and for HT Line only tension towers) from the edge of ROW, important milestone, intersections, cross drainage works any other structure existing of proposed etc. Certificate for

परियोजना निवेशक/ Philest Director भगतीय राष्ट्रीय राज्यार्ग प्राधिकरण ा ional Highway Authority olandia मुरादायाय/Moradabad

	(ii) for 6- laning		
	(a) Where feasibility is available " I do certify that there will no		
	hindrance to propose 6 laning based on the feasibility report		
	considering proposed structures at the said location "		2
	(b) In case feasibility report is not available "I do certify that sufficient ROW is available at site for accommodating of six -		
	laning"	A.	160
<u>5</u>	If NH section proposed to be taken up by NHAI on BOT basis-a-clause is to be	N/A	
	inserted in the agreement "The permitted highway on which licensee has been		
	granted the right to lay over head electrical line has also been granted as a		
	right of way to the concessionaire under the concession agreement for up-	e	
9	gradation of.	6	
	(Aligarh to Dibai section from KM 37 to Km 38 NH no 93(509), on build operate		
	and transfer basis) and therefore the licensee shall honour the same."		
<u>6</u>	Who will supervise the work of laying of overhead electrical line.	GTL	
7	Who will the sign the agreement on behalf of overhead electrical line agency	Associate Manager, GTL	
8	Who will ensure that the defect in road portion after laying of over head	GTL	
	electrical are corrected and if not corrected that what action will be taken.	* ,	
9	Who will pay the claims for damages done / disruption in working of	GTI.	
	concessionaire, if asked by the concessionaire.		
<u>10</u>	A certificate from PD that he will enter the proposed permission in register of	NHAI	
	record of the permission in the prescribed performa (copy enclosed)		
11	If any previous approval for laying of overhead electrical line then photocopy	N/A	
•	of register of records of permission accorded as maintained by PD may be		
	enclosed.		-

परियोजना निवेशक LProject Director भारतीय राष्ट्रीय राजमार्ग प्राधिकरण National Highway Authority of India मुरादाबाद /Moradabad

TO AP195B FOR IN BETWEEN TOWER NO -AP195A 38 MILESTONE) OVERHEAD NH-91

