

भारतीय राष्ट्रीय राजमार्ग प्राधिकरण (सड़क परिवहन एवं राजमार्ग मंत्रालय, भारत सरकार) दूर National Highways Authority of India (Ministry of Road Transport & Highways, Govt. of India) देल (Ministry of Road Transport & Highways, Govt. of India) क्षेत्रीय कार्यालय–पश्चिम उ०प्र०, लखनऊ Regional Office - West UP, Lucknow. 3/248, विशाल खण्ड, गोमती नगर, लखनऊ–226010 (उ.प्र.) 3/248, Vishal Khand, Gomti Nagar, Lucknow-226010 (UP) 19001/1/RO-W-UP/NH-334B/11.495-11.540/220KV/ 960.

दूरभाष / Phone : 0522-4960291 टेलीफैक्स / Fax : 0522-4950680 ई—मेल / E-mail : rowestup@nhai.org rowestup@gmail.com वेबसाइट / Website : www.nhai.gov.in

Dated: 04.10.2021

Invitation of Public Comments

<u>Sub</u>: Permission for erection/installation of 220 KV D/C Baghpat PG (400)-Modipuram-II (200) Transmission line for Overhead crossing on NH-334B (Meerut-Baghpat) between Ch. No. 11+495 & 11+540 near village-Janee Khurd, district-Meerut in the State of Uttar Pradesh- reg.

The Executive Engineer, Electricity Transmission Division, UPPTCL, Meerut has submitted the proposal through Project Director, Baghpat for the permission of erection/installation of 220 KV D/C Baghpat PG (400)- Modipuram-II (200) Transmission line for Overhead crossing on NH-334B (Meerut-Baghpat) between Ch. No. 11+495 & 11+540 near village-Janee Khurd, district-Meerut in the State of Uttar Pradesh.

2. From the submitted proposal, it is seen that structures (Transmission Towers) on either side are being erected at distance of 86m & 132.00m respectively from either side of NH boundary. Crossing span of the structure is 244m. Further, the minimum vertical clearance of 16.80m between the lowest conductor of the proposed line and NH carriageway shall be maintained. However, the proposed transmission line shall be crossing the National Highway at 85⁰ angle.

3. As per the guidelines, issued by the Ministry vide OM No.RW/NH-33044/29/2015/ S&R(R) dated 22.11.2016, the application shall be put out in the public domain for 30 days for seeking claims and objections (on grounds of public inconvenience, safety and general public interest).

4. In view of the above, comments of the public on the above application is invited to the below mentioned address, which should reach by this office within 30 days from the date of publication beyond which no comments shall be entertained.

The General Manager cum Regional Officer, National Highways Authority of India Regional Office, UP-West, Lucknow 3/248, Vishal Khand, Gomti Nagar Lucknow-226 010

This issues with the approval of RO-West (UP).

Encl: As above.

(Anuj Kumar Singh) Manager (T) For RO-UP (West)

Copy to:

- 1. Web Admin, NHAI-HQ- with request for uploading on the NHAI website.
- 2. The Technical Director, NIC, Transport Bhawan, New Delhi with request for uploading on the Ministry's website.
- 3. The Executive Engineer, Electricity Transmission Division, UPPTCL, Meerut for information.
- 4. The Project Director, NHAI, PIU-Baghpat for information.

"Building a nation, not just Roads."

मुख्यालय : प्लाट सं0 जी—5 एवं 6, सेक्टर—10, द्वारका, नई दिल्ली — 110 075, दूरभाष : 91—11—25074100 / 200 Head Office : Plot No. G-5 & 6, Sector - 10, Dwarka, New Delhi - 110 075 Phone : 91-11-25074100/200 FOR NH -334B Road Crossing by 220 KV DC BAGHPAT PG (400)-MODIPURAM (220) II T/L

S.NO.	DESCRIPTION	DETAILS
1.	National Highway Number	NH 334B
2.	Name of Crossing	MEERUT-BAGHPAT
3.	SYSTEM OF SUPPLY (i.e VOLTAGE)	Rated system Voltage – 220 KV.
	FREQUENCY NO.OF PHASES, WHETHER	Frequency – 50 Hz 3- Phase.
	NEUTRAL IS EARHTED OR NOT	Neutral effectively earthed.
4.	Position of towers	BETWEEN LOC. NO.107(DC+5) &108 (DC+5)
5.	NORMAL SPAN OF CONDUCTOR	380 M.
6.	MAX.SAG AT NORMAL SPAN	11.75M
7.	CROSSING SPAN	244 M.
8.	Preceding span	348 M.
9.	Succeeding span	280M.
	Height of structure above ground and below ground separately and details of foundation	A) Location No. 107 (DC+5) height above GL 44.390 M depth below GL 3.00M.
10.		B) Location No. 108 (DC+5)
		height above GL 44.390 M depth below GL 3.00M
11.	MILE STONE NO	NA
12.	CLEARANCE OVER ROAD	16.80 M.
13.	Height above ground level of (1) Lowest conductor on insulator and (2) guard wire on bracket above ground level	24.215 M.
14.	Height of road level above ground level measured at the foot of the structure.	Location No.
		107 DC+5 = 1.25M. Location No.
		108 DC+5 = 1.25 M
15.	Angle of road crossing	850
1/	Distance of NH Boundary From center of tower	Loc. No. 107(DC+5) =132
16.		Loc. (Security Engineer 5) = 86
	1	Bowe ansulssion Corporation Ltd.
	IN .	Projec

Optim

4 9:00

Sh cm

Project Director National Highway Authority of India PIU-Baghpat

17.	Perpendicular distance from center of tower to center of road	Loc. No. 107(DC+5) = 145 M. Loc. No. 108 (DC+5) = 99 M
18.	Protection of assembly to the line	Anti Climbing devices provided
19.	No. of stay required	NO.
20.	Minimum Factor of Safety	2.
21.	Size of power conductor mm.	ACSR ZEBRA (Conductor dia.28.62MM
22.	OPGW	24 FIBRE
23.	FOUNDATION TYPE	FS AS PER REQUARIED
24.	PLAN PAPER DIAGRAM	PROFILE(ENCLOSED)
	EARTHING	PIPE TYPE EARTHED

Transmission Division

Offit

82 mg

D

Project Director National Highway Authority of India PIU-Baghpat -